

# DOTA

A clear, grazing or diffusive lighting,displaced on turning axis. The aluminum support allows light beams and source orientation, granting a complete rotation and creating accent or wide lighting. DOTA is light always on the move. It is available in different versions, both in white or black finish.

SLIM SIZE

The track system is more slim in low voltage



EASY INSTALLATION



RA

High CRI up to 97



RELIABLE

Branded component ensure the lighting have reliable quality




### LOW VOLTAGE TRACK LIGHT

### GAMMA

Product series	DOTA
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K,
	3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Intergrated
Luminaire colour	RAL 9005 jet black
	RAL 9016 traffic white
	Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On Request
Weight	Approx.0.45kg
Test seal	ERI         C €         IP20         (100,000)         (100,000)






#### Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	Function
GMT201	6W	80LM/W	L112*W22.5*H86	24°	48V	90/98	on/off Dim/dali/0-10V Zigbee

24°-3000K-CRI90




### LOW VOLTAGE TRACK LIGHT

## GAMMA

Product series	DOTA
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K,
	3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Intergrated
Luminaire colour	RAL 9005 jet black
	RAL 9016 traffic white
	Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On Request
Weight	Approx.0.57 kg
Test seal	IP20         (1) <th(1)< th=""> <th(1)< th=""></th(1)<></th(1)<>






#### Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	Function
GMT201	12W	80LM/W	L220*W22.5*H86	24°	48V	90/98	on/off DIM/DALI/0-10V Zigbee

24°-3000K-CRI90



79