



## DOTAGE

DOTAGE as linear lighting which have widely beam angle 120D , apply as general light . Have three different choice on the size and power.



**SLIM SIZE**  
The track system is more slim in low voltage



**EASY INSTALLATION**




**RA**  
High CRI up to 97




**RELIABLE**  
Branded component ensure the lighting have reliable quality




FOOD



FASHION




SHOP



AUTOMOBILE


Product series	DOTAGE
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Intergrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On Request
Weight	Approx.0.16kg
Test seal	<div> <div>ERL</div> <div>CE</div> <div>IP20</div> <div> </div> <div> </div> <div> </div> <div> <div>TM-21</div> <div>100,000</div> </div> </div>




## Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	Function
GMT301	10W	80LM/W	L300*W23*H26	110°	48V	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

110°-3000K-CRI90




Product series	DOTAGE
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Intergrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On Request
Weight	Approx.0.16kg
Test seal	<div><div>ENEC</div><div>CE</div><div>IP20</div><div></div><div></div><div></div><div>TM-21 100,000</div></div>





Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	Function
GMT301	12W	80LM/W	L300*W23*H26	110°	48V	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

110°-3000K-CRI90



Product series	DOTAGE
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 3500K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Intergrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On Request
Weight	Approx.0.16kg
Test seal	



## Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	Function
GMT301	20W	80LM/W	L600*W23*H26	110°	48V	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

110°-3000K-CRI90

