



MEGA-C

MAGA-C made of die-cast aluminium and thermoplastic material. Opti Beam inter-changing reflectors with high luminous efficiency and uniform distribution.



FLEXIBLE INTSALLTION

Inclination of 90° on horizontal plane and 360° rotation around the vertical axis, with mechanical aiming lock.



HIGH CRI

LED versions with high color rendering index. High visual comfort




RELIABLE

Branded component ensure the lighting have reliable quality.



FOOD



FASHION




SHOP



AUTOMOBILE

Product series	MEGA-C
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 4000K, 5000 K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black
	RAL 9016 traffic white
	Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On request
Weight	Approx.0.1kg
Test seal	<div><div>ERL</div><div>CE</div><div>IP20</div><div></div><div></div><div></div><div>TM-21 100,000</div></div>



Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT501	5W	70-80LM/W	30*H80mm	15°/24°/36°/55°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

18°-3000K-CRI90




24°-3000K-CRI90



36°-3000K-CRI90



Product series	MEGA-C
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 4000K, 5000 K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On request
Weight	Approx.0.14kg
Test seal	<div><div>ERL</div><div>CE</div><div>IP20</div><div></div><div></div><div></div><div>TM-21 100,000</div></div>



Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT501	10W	70-80LM/W	40*H100mm	15°/24°/36°/55°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

18°-3000K-CRI90




24°-3000K-CRI90



36°-3000K-CRI90



Product series	MEGA-C
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track, not suitable for vertical mounting
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 4000K, 5000 K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black
	RAL 9016 traffic white
	Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On request
Weight	Approx.0.2kg
Test seal	<div><div>ERL</div><div>CE</div><div>IP20</div><div></div><div></div><div></div><div>TM-21 100,000</div></div>



Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT501	15W	70-80LM/W	52*H120mm	15°/24°/36°/55°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

18°-3000K-CRI90



24°-3000K-CRI90



36°-3000K-CRI90

