



MAGEN

MAGEN is the simplest of cylinders. The exterior is clean with no visible seams or hardware. Inside, a wealth of technology remains hidden.



STRUCTURE

Machined aluminum tube offered with textured black, white finish. MAGEN can be specified with 2 baffle finishes: white or black.



OPTIC

Designed with narrow or medium beam angle, to meet all applications. Optical choice of clear, frosted or honeycomb lenses available.



RA

High CRI up to 97




Reliable

Branded component ensure the lighting have reliable quality.



FOOD



FASHION




SHOP



AUTOMOBILE


Product series	MAGEN
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 3500 K, 4000 K, 5000K
Cooling	Passive
Supply unit	Driver Intergrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On Request
Weight	Approx.0.31kg
Test seal	<div> <div>ERL</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div></div> <div>TM-21 100,000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	Function
GMT601	10W	80LM/W	30*300mm	15°/24°/36°	48V	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE


15°-3000K-CRI90




24°-3000K-CRI90



36°-3000K-CRI90




Product series	MAGEN
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 3500 K, 4000 K, 5000K
Cooling	Passive
Supply unit	Driver Intergrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On Request
Weight	Approx.0.41kg
Test seal	<div> <div>ERL</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div>SDCM < 3</div> <div>TM-21 100,000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	Function
GMT601	15W	80LM/W	40*300mm	15°/24°/36°	48V	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE


15°-3000K-CRI90




24°-3000K-CRI90



36°-3000K-CRI90




Product series	MAGEN
Application areas	Accent lighting
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700 K, 3000 K, 3500 K, 4000 K, 5000K
Cooling	Passive
Supply unit	Driver Intergrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	48V
Lighting controls	On Request
Weight	Approx.0.51kg
Test seal	<div> <div>ERL</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div></div> <div>TM-21 100,000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	Voltage	CRI	Function
GMT601	20W	80LM/W	52*300mm	15°/24°/36°	48V	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90



24°-3000K-CRI90



36°-3000K-CRI90

