



BLEEM

BLEEM stands for compact and modern design that fits into every shop design. With its slim

proportions the LED luminaire sets modern accents. At the same time the customer's customised colour scheme can be incorporated into the luminaire design by the lateral lug being available in any colour required.



SPECIAL LENS

The light transmission is three-dimensional and uniform, and the light shadow contour is more beauty package



POWER PACKAGE

- White light colours up to 4000 lm
- Special light spectrums for the fresh-food area up to 4000 lm



EFFICIENT LIGHTING

6 % more light and 34 % more efficiency (in comparison to HIT 70 W)



ELEGANT DESIGN

Classic design with elegant proportions – Bleem fits into every shop design




WELL PROTECTED


Optional glass cover to protect from dirty




FOOD










FASHION




SHOP



AUTOMOBILE

Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.4KG
Test seal	      




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT301	15W	120LM/W	Ø55*140mm	15°/24°/36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Acessories




SOLITE
SOFTENING
LENS



HONEY
COMB

Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.4KG
Test seal	<div> <div>ERC</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div></div> <div>TM-21 100,000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT301	18W	120LM/W	Ø55*140mm	15°/24°/36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90

24°-3000K-CRI90


36°-3000K-CRI90










Accessories




SOLITE
SOFTENING
LENS






HONEY
COMB

Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.45KG
Test seal	      





Code composition/ Composizione del codice


Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT301	20W	120LM/W	Ø65*150mm	15°/24°/36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90	24°-3000K-CRI90	36°-3000K-CRI90
		

Acessories

	SOLITE SOFTENING LENS		HONEY COMB
---	-----------------------------	---	---------------

Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.5KG
Test seal	<div> <div>ERC</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div></div> <div>TM-21 100,000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT301	24W	120LM/W	Ø65*150mm	15°/24°/36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Acessories




SOLITE
SOFTENING
LENS



HONEY
COMB

Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.67KG
Test seal	<div> <div>ERC</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div></div> <div>TM-21 100,000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT301	28W	120LM/W	Ø75*160mm	15°/24°/36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB

Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.67KG
Test seal	<div> <div>ERC</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div></div> <div>TM-21 100,000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT301	30W	120LM/W	Ø75*160mm	15°/24°/36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB

Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.7KG
Test seal	<div> <div>ERC</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div></div> <div>TM-21 100.000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT301	30W	120LM/W	Ø85*170mm	15°/24°/36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Accessories




SOLITE
SOFTENING
LENS



HONEY
COMB

Product series	BLEEM
Application areas	Accent lighting
Pan/tilt range	355° turning range, 180° swivel range
Mounting	Power Track
Lighting technology	LED
LED Luminous Flux Class	120LM/W
Light colour White	2700K, 3000K, 4000K, 5000K
Cooling	Passive
Supply unit	Driver Integrated
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On request
Weight	Approx. 0.8KG
Test seal	<div> <div>ERC</div> <div>CE</div> <div>IP20</div> <div></div> <div></div> <div></div> <div>TM-21 100,000</div> </div>




Code composition/ Composizione del codice

Model	Power	Light flux	Size	Beam Angle	CRI	Function
GMT301	35W	120LM/W	Ø85*170mm	15°/24°/36°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE

15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Accessories



SOLITE
SOFTENING
LENS



HONEY
COMB